

Array™

luxury vinyl tile & plank

Color shown is 500 Grey Skies

Array Luxury Grout Premixed Ready-To-Use Grout

MADE IN CANADA | PROTECT FROM FREEZING

Description	Premixed sanded, acrylic grout.	
Unit Size	1 gallon	
Use	For grouting joints 1/16" to 1/4" wide.	
Limitations	Not recommended for exterior use, shower floors or underwater use.	
Coverage	Joint Width	Approximate Coverage 16" x 16" Tile
	1/16" (1.6mm)	450 sq. ft./gal. (42m ²)
	1/8" (3.2mm)	325 sq. ft./gal. (31m ²)
	3/16" (4.8mm)	275 sq. ft./gal. (26m ²)
	1/4" (6.4mm)	225 sq. ft./gal. (21m ²)
Applicator	Hard rubber float or green epoxy float.	
	Cleanup with firm sponge and 3M® white pad.	
Working Time	10 minutes – for best results apply grout in a 6-10 sq. ft. area on floors and clean-up immediately.	
Set up Time	8 hours	
Cleaning	Wet - Water	
	Dry - Household ammonia cleaner.	
	Do not use grout haze removers.	
Tracers	N/A	
Shelf Life	1 year if unopened	
Freeze/Thaw Stability	Yes	
Flammable	No	
Cautions	Potential skin, eye and respiratory irritant	

Colors



Resilient Grout

shawfloors.com

Array Luxury Grout 055VS | premixed ready-to-use grout

ARRAY GROUT IS A SANDED ACRYLIC GROUT

- The sanded feature gives the grout a beautiful texture and enhances its durability under foot.
- The acrylic feature makes the grout flexible which allows it to stay in the grout joint. This prevents grout from cracking.
- Non-acrylic grouts (many different kinds – latex based) tend to crack over a period of time due to the shifting of the sub-floor.
- Epoxy grouts are used but they are hard to install and expensive.

USE ARRAY GROUT WITH CONFIDENCE IN ANY INSTANCE YOU WOULD USE THESE PRODUCTS

- Precision Components Pre-mixed Grout for LVT
- Armstrong S-693 Sanded Acrylic Grout (for Alterna)
- Mannington Adura Grout
- Congoleum Duraceramic Premixed Grout
- Metroflor Tru-Grout
- Mapei Luxury Vinyl Tile Grout

Installation

Array Grout is a specially developed acrylic sanded grout designed to complement Array Luxury Vinyl Tile. It is premixed and easy to install.

Technical Notes

- Use at temperatures above 50°F (10°C) or below 90°F (32°C).
- For interior use only.
- Not recommended for underwater areas.
- Drying time may vary, depending on ambient temperature and humidity.

Surface Preparation

Before grouting, make sure tiles are firmly set and clean. All grout joints must be clean and dry.

Application

1. Work only a small area at a time – 6 to 9 tiles.
2. Using a rigid grout float, fully pack the premixed grout into the grout joints.
3. Make sure all joints are free of gaps and voids.
4. Remove excess grout from the tile, moving the float edge diagonally across the tile surface while the premixed grout is still fresh.
5. The grout surface should be flush with the tile edge.
6. Do not “full spread”. Use the narrow edge of the grout float using only enough grout to fully pack the joint. The less grout on the tile face the easier clean up will be.

Cleaning

1. Allow the grout to firm up prior to cleanup. The set time (3 to 5 minutes) may vary depending on temperature and humidity conditions.
2. Apply a very light film of water over the grouted tile surface using a spray bottle.
3. Allow the water to sit on the tile surface for 20 to 30 seconds.
4. Very gently, rub the haze grout using a clean, damp white cleaning pad.
5. Use a clean, damp, flat square sponge to slowly wipe diagonally across the tile, removing the remaining grout and water. Repeat until the surface is clean. Use two buckets of clean water – one for rinsing most of the grout residue and the other for moistening the sponge for the following cleanup.
6. Allow the grout to dry for 24 hours prior to final cleanup. Use a clean, damp, flat square sponge to wipe off the remaining grout haze.

Protection

Before allowing light traffic, protect for 24 hours. Wait at least 48 hours prior to moving any furniture on the floor.